



AT FSERIES

ATF M-V

MAZDA FORMULATION



For applications where Mazda ATF D-II, ATF M-III,ATF M-V, ATF FZ, ATF F-1, ATF S-1, ATF N-1, ATF A7, and Mazda ATF 3317 specifications are recommended.

- MEETS MAZDA SPECIFICATIONS
 - Part number 4010M

SP ATF

HYUNDAI/KIA FORMULATION



For applications where Hyundai/Kia SP-IV (00232-1904/04500-00115), SP-IV M (SP4-M), SPH-IV, SP-IV-RR, SP-III, Dex-II/SP-II, JWS 3314, NWS 9638, 040000C90SG, and NUMM040 CH20 Red-1 specifications are recommended.

- MEETS HYUNDAI/KIA SPECIFICATIONS
 Part number 4005M
 - ATF Z1/DW-1

HONDA FORMULATION



For applications where Honda ATF-Z1 (except in CVTs),ATF Ultra II, DW-1, Type 3.0 and Honda Type 3.1 : 08263-999-01HE (EU), 08200-9017 (USA) (ZF LifeguardFluid 9) (ZF No. AAO1.500.001) specifications are recommended.

MEETS HONDA SPECIFICATIONS
 Part number 4008M

8&9 SPEED

ZF FORMULATION



8&9 Speed automatic transmission fluid is formulated to meet the stringent specifications of the ZF Group including all ZF 3 & 4 speed transmission, ZF 6 speed transmission, ZF 8 & 9 speed transmissions, and where ZF TE-ML 05L, ZF TE-ML 09, ZF TE-ML 11A, 11B, ZF TE-ML 21L, and serivice-fill for 8&9 speed step-ATs are recommended.

- MEETS ZF SPECIFICATIONS
 Part number 4013M
 - ATF + 3, +4

JEEP FORMULATION



For applications where Jeep ATF +3, +4, 05127382AA, 68043742AA, and 68171866AA specifications are recommended.

- MEETS JEEP SPECIFICATIONS
 Part number 4002M
 - Fait number 4002m

ATF JWS

BMW FORMULATION



For applications where BMW JWS 3309 (T-IV), BMW LA2634, BMW LT71141 (ZF 5 HP 18FL/19FL/24A), BMW ZF 5HP18FL, 5HP24, 5HP30, BMW 7045E, ETL 8072B, MINI, BMW 83 22 0 142 516 (ZF Lifeguard Fluid 6), BMW ATF 6, and Bosch TE-ML 09 specifications are recommended.

- MEETS BMW SPECIFICATIONS
 - Part number 4003M

ATF +

CHRYSLER FORMULATION




For applications where Chrysler ATF+, +2, +3 (MS 7176E), +4 (MS 9602), Chrysler/Dodge MOPAR AS 68 RC and AS 69 RC (T-IV), JWS 3309, Jeep 05127382AA, 68157995AA, 68043742AA, 68157995AB, 68218925AA, MOPAR SP IV, 68171866AA, and 68171869AA specifications are recommended.

- MEETS CHRYSLER SPECIFICATIONS
 - Part number 4004M


Specially Formulated

- Full synthetic maximum wear protection
- Outstanding low temperature flow properties



1 U.S. QUART







Unit 407 - 204 Cayer st., Coquitlam BC, V3K5B1, Canada

www.motosel.com | info@motosel.com | 1.888.668.6463