

# Motosel SAE 5W-30 EURO

## ULTRA EURO PASSENGER CAR MOTOR OIL

### MOTOSEL SAE 5W-30 ULTRA EURO Motor Oil

Motosel Full Synthetic SAE 5W-30 Motor Oil is a superior quality multi-grade motor oil designed with a state-of-the-art low friction additive system for maximum engine protection even under the toughest driving conditions. It outperforms conventional motor oil, reduces friction and wear at start-up and protects your engine against performance robbing sludge and varnish deposits.

Motosel Full Synthetic Motor Oil is recommended for turbo-charged and high-powered passenger car, truck, sport utility vehicle and other mobile or stationary engines.

### Benefits and Applications

- Designed especially for European gasoline and diesel engines
- More robust oil for longer drain intervals
- Enhanced oxidative stability, emission system and wear protection
- Maximum engine wear, corrosion, and rust protection and cleanliness
- Aggressive resistance to sludge and varnish deposits formation
- Lower pour point reduces start-up wear during cold weather

Meets the following performance specification :

API SP  
ILSAC GF-6A  
GM 6094M, Chrysler  
MS6395M, Ford  
WSS-M2C929A,  
WSS-M2C946A,  
Porsche, Renault



- #M-0634 / 1Qt
- #M-1074 / 5Qt
- #M-0320 / 5Gal
- #M-0326 / 22.7L Box
- #M-0338 / 16Gal
- #M-0340 / 208L Drum
- #M-0199 / Bulk

### TYPICAL CHARACTERISTICS - 5W-30 EURO

SAE GRADE	FULL SYN	5W-30
API SERVICE		SP/GF-6A
API Gravity	ASTM D287	35.58
Flash Point, COC °C/°F	ASTM D92	227 / 440.6
Pour Point, °C/°F	ASTM D97	-46 / -50.8
Viscosity @ 40°C, cSt	ASTM D445	61.8
Viscosity @ 100°C, cSt	ASTM D445	10.8
Viscosity Index	ASTM D2270	165
CCS, mPa·sec °C max	ASTM D5293	6200 @ -30
Total Base No. TBN	ASTM D2896	8.2

Typical test data are average values only. Minor variations, which do not affect performance, may occur. You should consult your owner's manual to verify proper fluid recommendation for your particular vehicle.

**HANDLING AND SAFETY INFORMATION** - Refer to MOTOSSEL (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.



WWW.MOTOSEL.COM  
INFO@MOTOSEL.COM  
+1-888-668-6463