

MOTOSEL SAE 0W-40 ULTRA EURO Motor Oil

MOTOSEL SAE 0W-40 ULTRA EURO Motor Oil is an advanced synthetic formula designed to exceed the most car manufacturer standards and engineered to keep engines closer to factory clean. This insures a better protected, more efficient engine, which delivers premium performance.

Motosel Ultra Euro is designed for extended drain intervals as suggested by European automobile manufacturers.

Benefits and Applications

- Reduces dep osits by isolating and dissolving contaminants safely into the oil
- Prevents sludge build-up, damaging deposits, corrosion and engine wear
- Provides proven protection for critical engine parts
- Helps protect emission systems
- Provides oil stability and endurance under extreme conditions, which deters thermal breakdown

Approved against the following performance specifications:

- API SP
- ACEA C3-10
- Porsche A40
- MB-Approval 229.51
- Volkswagen VW 502.00
- Volkswagen VW 505.00
- Volkswagen 50501
- BMW Longlife-04



- #M-0135 / 1Qt
- #M-0544 / 4Qt
- #M-0032 / 5Qt
- #M-0142 / 5Gal
- #M-0296 / 16Gal
- #M-0147 / 208L Drum
- #M-0154 / Bulk

TYPICAL CHARACTERISTICS - EURO SAE 0W-40 FULL SYNTHETIC

SAE GRADE		0W-40
API SERVICE		SP
Specific Gravity 15.6°C	ASTM D445	N/A
Flash Point, COC °C	ASTM D97	201
Pour Point, °C	ASTM D4683	-48
Viscosity @ 40°C, cSt	ASTM D445	86.2
Viscosity @ 100°C, cSt	ASTM D93	15.1

Test Method ASTM - Typical test data are average values only. Minor variations, which do not affect performance, may occur.

HANDLING AND SAFETY INFORMATION - Refer to MOTOSEL (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.