

Motosel SAE 10W-30 HI-MI Synthetic Blend ENGINE OIL

Motosel Synthetic Blend High Mileage SAE 10W-30 Motor Oil is a premium quality multi-grade motor oil formulated with a low friction additive package designed especially for higher mileage engines. It outperforms conventional motor oil, reduces friction and wear at start-up and protects your engine against performance robbing sludge and varnish deposits even under the toughest driving conditions. Motosel High Mileage Motor Oil is recommended for passenger car, truck, sport utility vehicle and other engines with over 75,000 miles.

Motosel Synthetic Blend High Mileage SAE 10W-30 Motor Oil meets or exceeds ILSAC GF-6A and American Petroleum Institute (API) Resource Conserving SP service classifications and is compatible with all prior API categories. Motosel High Mileage Motor Oil has been field tested to be comparable to most American, Asian, European manufacturers' standards including Ford WSS-M2C205A, GM 6094M, Chrysler MS6395, and many other OEM's specifications where a synthetic blend API SP motor oil is recommended.

Benefits and Applications

- Motosel Synthetic Blend motor oil outperforms conventional oil
- Excellent wear, corrosion, and rust protection
- Exceptionally resistant to oxidation
- Excellent cold-crank capabilities
- Helps improve fuel economy

Meets the following performance specification :

API SP
ILSAC GF-6A
Ford WSS-M2C205A,
GM 6094M, Chrysler MS6395



- #M-0172 / 1Qt
- #M-0210 / 5Gal
- #M-0209 / 55Gal
- #M-0208 / Bulk

TYPICAL CHARACTERISTICS - 10W-30 HI-MI

SAE GRADE	FULL SYN	10W-30
API SERVICE		SP / GF-6A
API Gravity	ASTM D287	32.6
Flash Point, COC °C/°F	ASTM D92	237 / 458.7
Pour Point, °C/°F	ASTM D97	-39 / 38.2
Viscosity @ 40°C, cSt	ASTM D445	64.15
Viscosity @ 100°C, cS	ASTM D445	10.08
Viscosity Index	ASTM D2270	143
CCS, mPa-sec °C max	ASTM D5293	7000 @ -25
Total Base No. TBN	ASTM D2896	7.5

Typical test data are average values only. Minor variations, which do not affect performance, may occur. You should consult your owner's manual to verify proper fluid recommendation for your particular vehicle.

HANDLING AND SAFETY INFORMATION - Refer to MOTOSEL (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.



WWW.MOTOSEL.COM
INFO@MOTOSEL.COM
+1-888-668-6463