



HD ATF HEAVY DUTY FULL SYNTHETIC

FULL SYNTHETIC

HEAVY DUTY ATF TES - 668

Motosel Full Synthetic ATF-668 Automatic Transmission Fluid is the next generation of full synthetic transmission fluid engineered to meet or exceed Allison TES 668™ specification for use in on-highway heavy-duty automatic truck and bus transmissions. It has outstanding low-temperature flow properties, advanced anti-wear formulation, and excellent thermal and oxidation stability for longer service life, extended drain intervals, and enhanced transmission performance in all operating environments.

Motosel Full Synthetic ATF-668 Automatic Transmission Fluid meets or exceeds the performance levels of most American, Asian, and European manufacturers including: Allison TES-668™, H 40 EP™, H 50 EP™ and eGen Flex series on-highway products, Allison TES 295, Volvo 97341, Ford M, GM DEX-IIIH / IIG / IID, JASO M315 Type 1A, and comparable OEM specifications. It is suitable for all Allison 1000 Series™, 2000 Series™, 3000 Series™ and 4000 Series™ automatic transmissions.

Benefits and Applications

- Maximum heavy duty performance
- Excellent shear stability properties and viscosity retention
- Enhanced additives for longer service life and performance
- Long-lasting durability and extended drain intervals

COMPARABLE
PERFORMANCE LEVELS
INCLUDES :

Allison TES-668™
Allison TES 295
Volvo 97341, Ford M,
GM DEX-IIIH, JASO
M315 Type 1A

TYPICAL CHARACTERISTICS - HD ATF HEAVY DUTY FULL SYNTHETIC



#M-0474 / 5 Gallon

SERVICE GRADE	TEST METHOD	ATF TES 668
Color	Visual	RED
Viscosity @ 100°C, cSt	ASTM D445	6.88
Viscosity @ 40°C, cSt	ASTM D445	34
Viscosity Index	ASTM D2270	154
Pour Point, °C/°F	ASTM D97	-52 / -61.6
Flash Point, COC °C/°F	ASTM D92	222 / 431.6
API Gravity	ASTM D287	34.79
Brookfield Vis.cP @ -40°C	ASTM D2983	11.585

Typical test data are average values only. Minor variations, which do not affect performance, may occur. You should consult your owner's manual to verify proper fluid recommendation for your particular vehicle.

HANDLING AND SAFETY INFORMATION - Refer to MOTOSEL (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.



WWW.MOTOSEL.COM
INFO@MOTOSEL.COM
+1-888-668-6463