

# Motosel 75W-80 GL-4 FULL SYNTHETIC

## GEAR OIL

**MOTOSEL 75W-80 GL-4** Full Synthetic Transmission Fluid is high performance synthetic lubricant for certain manual transmissions, transfer cases, and gear boxes requiring specialized fluid meeting OEM specifications and the technical requirements of API GL-4.

**MOTOSEL 75W-80 GL-4** Full Synthetic Transmission Fluid is uniquely formulated for specific manual transmissions and gearboxes in passenger cars and light truck applications where non-EP lubricants are required. This product is recommended for use where manufacturers specify Synchronmesh fluid such as in certain General Motors and Chrysler applications. Many other manual transmission and transaxle applications are met including (but not limited to); BMW, Honda/Acura, Ford Focus, New Venture, Tremec, Land Rover, MG, Mini Cooper, and others. Do not use in engines, hypoid gear rear axles, limited slip, or wet clutch applications.

**Meets or exceeds the following specifications :**

- API GL-4 • BMW MTF LT-2, LT-3, LT-4
- FIAT MZ1, MZ60768 • FORD M2C200-C, M2C200-D
- GM 9985648, 9986105, 9985535, 1940004, 19259104 (BOT 303), 1940182, 1940764, 1940768
- Chrysler MS-9224, MS-9417 • HONDA MTF, MTF-II, MTF-III
- MB 235.10 • NISSAN MT-XZ, MT-XZ TL
- PSA B71 2330 • SPECIAL GEAR OIL MTF-94
- VOLVO 97309, 97309, 97310 • VW G 052 512, G 052 527, G 052 178, G 060 726,




#M-0540 / 5Gal  
#M-0561 / Bulk

### TYPICAL CHARACTERISTICS - 75W-80 GL-4

SAE GRADE	TEST METHOD	75W-80 GL-4
SAE Viscosity	J300	5W-30
SAE Viscosity	J306	75W-80
Specific Gravity @ 15.6°C	ASTM D4052	0.872
Viscosity @ 40°C (cSt)	ASTM D445	45.0
Viscosity @ 100°C (cSt)	ASTM D445	9.2
Viscosity Index	ASTM D2270	193
Pour Point, °C	ASTM D97	-48
Brookfield, cP max	ASTM D2983	50.000

Typical test data are average values only. Minor variations, which do not affect performance, may occur. You should consult your owner's manual to verify proper fluid recommendation for your particular vehicle.

**HANDLING AND SAFETY INFORMATION** - Refer to MOTOSEL (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.



[WWW.MOTOSEL.COM](http://WWW.MOTOSEL.COM)  
[INFO@MOTOSEL.COM](mailto:INFO@MOTOSEL.COM)  
+1-888-668-6463