

Motosel SAE 5W-40

Synthetic Blend ENGINE OIL

Motosel Synthetic Blend SAE 5W-40 Motor Oil a premium quality multi-grade motor oil designed with a state-of-the-art low friction additive system for superior engine protection even under the toughest driving conditions. It outperforms conventional motor oil, reduces friction and wear at start-up and protects your engine against performance robbing sludge and varnish deposits. Motosel Synthetic Blend Motor Oil is recommended for passenger car, truck, sport utility vehicle and other mobile or stationary engines.

Motosel Synthetic Blend SAE 5W-40 Motor Oil meets or exceeds American Petroleum Institute (API) SP service classification and is recommended for passenger cars, light trucks, and other four-stroke gasoline powered equipment wherever API SP/ ILSAC GF-6 certified oils are required. For all-season use in engines operating on gasoline, high-ethanol gasoline (E-85), propane, or compressed natural gas (CNG).

Motosel Synthetic Blend Engine Oils meet or exceed new car warranty requirements for North American, Asian, and European vehicles where API SP/ ILSAC GF-6 is referenced.

Benefits and Applications

- Motosel Synthetic Blend motor oil outperforms conventional oil
- Excellent wear, corrosion, and rust protection
- Exceptionally resistant to oxidation
- Excellent cold-crank capabilities
- Helps improve fuel economy

Meets the following performance specification :

**API SP, SN Plus, SN, SM, previous ILSAC GF-6A, GF-5, GF-4
Chrysler MS-6395
GM 6094M**



- #M-0355 / 1Qt
- #M-0592L / 5L
- #M-0593L / 1Qt
- #M-0356 / 5Qt
- #M-0549 / 4Qt
- #M-0357 / 5Gal
- #M-0556 / 4L

TYPICAL CHARACTERISTICS - 5W-40

SAE GRADE	5W-40	
API SERVICE		SP
API Gravity	ASTM D287	35.0
Flash Point, COC °C/°F	ASTM D92	205 / 401
Pour Point, °C/°F	ASTM D97	-38 / -36.4
Viscosity @ 40°C, cSt	ASTM D445	84.0
Viscosity @ 100°C, cS	ASTM D445	15.0
Viscosity Index	ASTM D2270	145
CCS, mPa-sec °C max	ASTM D5293	6200 @ -30
Total Base No. TBN	ASTM D2896	7.9

Typical test data are average values only. Minor variations, which do not affect performance, may occur. You should consult your owner's manual to verify proper fluid recommendation for your particular vehicle.

HANDLING AND SAFETY INFORMATION - Refer to MOTOSEL (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.



WWW.MOTOSEL.COM
INFO@MOTOSEL.COM
+1-888-668-6463