

# Motosel SP ATF

## AUTOMATIC TRANSMISSION FLUID

### Motosel Full Synthetic Automatic Transmission Fluid

is formulated to meet the stringent specifications of Hyundai/Kia including Hyundai/Kia SP-IV (00232-1904/04500-00115), SP-IV M (SP4-M), SP-IV-RR, SP-III, Dex-II/ SP-II, JWS 3314, NWS 9638, 040000C90SG, and NUMMO40 CH20 Red-1. It provides extreme protection including additional oxidation control, excellent low temperature and superior shear stability performance in modern passenger car, flex-fuel vehicle, hybrid, truck, and sport utility vehicle transmissions. It is suitable for use in automatic transmissions calling for GM DEXRON® II/III/IIIE/IIIH, Allison C-3 & C-4, CAT TO-2, Ford MERCON®LV, Chrysler ATF+3 +4, Honda Z-1, DW-1, JASO 1A, 2A, Nissan Matic Fluids, Toyota T-III, T-IV, WS and many other American, Asian and European OEM's performance standards including Mercedes Benz NAG 1, MAN 339A, Mazda, Mitsubishi, Subaru, Porsche, Voith 55.6335, VW, ZF TE-ML 21L, ZF 8 & 9 speed and BMW 4- and 5-speed automatic transmission specifications.



#4005M / 1Qt  
 #M-0234 / 5Gal  
 #M-0240 / 22.7L  
 #M-0235 / 55Gal  
 #M-0236 / Bulk

### Benefits and Applications

- Full synthetic maximum corrosion, wear, and rust protection
- Outstanding low temperature flow properties
- Enhanced friction additives and oxidation stability for longer fluid life
- Smooth shifting and reduce shudder performance
- High compatibility - suitable for use in most applications

### Hyundai/Kia Formulation:

for applications where Hyundai/Kia SP-IV (00232-1904/04500-00115), SP-IV M (SP4-M), SP-IV-RR, SP-III, Dex-II/ SP-II, JWS 3314, NWS 9638, 040000C90SG, and NUMMO40 CH20 Red-1 specifications are recommended.

### TYPICAL CHARACTERISTICS - SP ATF

SAE GRADE	TEST METHOD	SP ATF
Colour	Visual	Red
Viscosity @ 100°C, cSt	ASTMD 445	7.0
Viscosity @ 40°C, cSt	ASTMD 445	32.9
Viscosity Index	ASTMD 2270	180
Pour Point, °C/°F	ASTMD 97	-51/-59.8
Flash Point, COC °C/°F	ASTMD 92	204 / 399.2
API Gravity	ASTMD 1298	32.6
Brookfield Vis.cP @ -40°C	ASTMD 2983	16200

Typical test data are average values only. Minor variations, which do not affect performance, may occur. You should consult your owner's manual to verify proper fluid recommendation for your particular vehicle.

**HANDLING AND SAFETY INFORMATION** - Refer to MOTOSEL (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.



WWW.MOTOSEL.COM  
 INFO@MOTOSEL.COM  
 +1-888-668-6463