

Motosel MV-36

HYDRAULIC OIL

MOTOSEL MV-36 Hydraulic Oil

MOTOSEL MV-36 Hydraulic Oil is a Multi-viscosity, anti-wear hydraulic oil, designed for use in hydraulic systems subjected to wide variations in ambient and operating temperatures. Multi-viscosity characteristics reduce the risk of breakdown in high pressure/high load hydraulic systems which operate over a wide temperature range. Anti-wear additive package reduces wear by protecting surfaces when load causes breakdown of the lubricant film. Rust and corrosion inhibitors give good protection against corrosion of both steel and copper. Good hydrolytic stability and water separation characteristics help provide filterability in the presence of water contamination. Good anti-foam and air release properties ensure smooth operation and system efficiency. Oxidation inhibitors help reduce oil thickening and deposit formation in service, minimizing the need for unscheduled change of hydraulic fluid.

Benefits and Applications

- Industrial hydraulic equipment subject to wide variation in temperatures.
- Hydraulics of mobile, construction and agricultural equipment where a water separating oil is required.
- Hydraulic systems with vane, gear or piston pumps.
- Forklift trucks (in refrigerated areas).
- Plastic injection moulding machines.
- Marine deck equipment, steering gears, thrusters and automatic controls.
- Machine tools.
- Enclosed gear systems (dependent on load).




#M-0512 / 4Qt
#M-0249 / 5Gal
#M-0108 / Bulk

TYPICAL CHARACTERISTIC MV-36 HYDRAULIC OIL

ISO GRADE	MV-36
Flash Point, °C/°F	225 / 437
FZG, Fail Load Stage	12
Pour Point, °C/°F	-46 / -50.8
Viscosity @ 100°C, cSt	6.5
Viscosity @ 40°C, cSt	32.5
Viscosity Index	154
Zinc Content, m%	0.042
Oxidation Stability, hours	6500

Test Method ASTM - Typical test data are average values only. Minor variations, which do not affect performance, may occur.

HANDLING AND SAFETY INFORMATION - Refer to MOTOSEL (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.



WWW.MOTOSEL.COM
INFO@MOTOSEL.COM
+1-888-668-6463