

MOTOSEL Continuously Variable Transmission Fluid

MOTOSEL CVT Premium Transmission Fluid is specially formulated with a highly advanced additive package to meet the performance requirements of a wide variety of vehicles equipped with push-belt CVTs. MOTOSEL CVT Transmission Fluid has enhanced critical frictional characteristics that will provide a longer service life with improved high and low temperature protection. MOTOSEL CVT Transmission Fluid provides smooth shifting, a high level of both torque capacity and outstanding anti-shudder performance for enhanced driving comfort.

Benefits and Applications

- Higher safety factor
- · Longer transmission life
- Extended service interval
- Excellent extreme pressure and anti-wear performance for the better life and protection
- Enhanced oxidative stability for longer fluid life and extended service interval
- Seal compatibility for better leakage prevention
- CVT fluid recommended for use where the following fluids are called for:
 - BMW Mini Cooper EZL 799 Dodge/Jeep NS-2, CVTF+4 CVT30, Mercon C GM/ Saturn DEX-CVT
 - Honda HMMF, HCF-2 Hyundai/ Kia CVT applications (SP-CVT 1) Mitsubishi CVTF-J1,
 - Nissan NS-2, NS-3 Suzuki TC, NS-2, CVT Green 1, CVT Green 2 Toyota TC, FE



TYPICAL CHARACTERISTICS - CVT FLUID

GRADE	сут
Color	Red
Viscosity @ 100°C, cSt	212
Viscosity Index	185
Flash Point, COC °C/°F	214 / 417.2
Specific Gravity @ 15.6/15.6°C	0.926
API Gravity	21.30
Brookfield Viscosity, cPat-40°C	12980
Max Handling Temp °C/°F	60 / 140

Test Method ASTM - Typical test data are average values only. Minor variations, which do not affect performance, may occur.

HANDLING AND SAFETY INFORMATION - Refer to MOTOSEL (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.

