

MOTOSEL Premium ATF Type A

Automatic Transmission Fluid is an economical fluid blended from quality base oils for use in older automatic transmission requiring Type A Fluid and/or where fluid leakage and consumption is a problem. USGLOBAL Type A ATF is red dye to aid in leak detection. Type A ATF fluids are not recommended for use where DEXRON® or MERCON® fluids are specified.

Benefits and Applications

- · All-temperature, year-round protection and performance
- Smoother shifting performance and positive lockup to reduce shudder
- · Extended service interval
- Excellent extreme pressure and anti-wear performance for the better life and protection of transmission
- Seal compatibility for better leakage prevention



TYPICAL CHARACTERISTICS - TYPE A

GRADE	TYPE A
Color	Red
Viscosity @ 100°C, cSt	7.2
Viscosity @ 40°C, cSt	36.0
Viscosity Index	150
Pour Point, °C/°F	-40 / -40
Flash Point, COC °C/°F	160 / 320
API Gravity	31.4

Test Method ASTM - Typical test data are average values only. Minor variations, which do not affect performance, may occur.

HANDLING AND SAFETY INFORMATION - Refer to MOTOSEL (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.

