MOTOSEL Full Synthetic SAE 10W-60 Motor Oil

MOTOSEL Full Synthetic SAE 10W-60 Motor Oil is in engine technology have led to increased power and efficiency, meaning engines work harder and under higher pressures than ever before. The only thing keeping metal engine components apart is the oil, so it needs to be strong and remain strong.

MOTOSEL Full Synthetic SAE 10W-60 Motor Oil is our strongest and most advanced range of engine oils.

Benefits

MOTOSEL Full Synthetic SAE 10W-60 Motor Oil provides outstanding oil strength, giving you the confidence to demand maximum engine performance from sports cars, competition and the latest technology high powered engines which operate under higher pressures requiring an oil with unsurpassed strength and performance credentials.

- Maximises short and long term engine performance
- Reduces engine deposits to help maximise engine response
- Delivers unsurpassed levels of protection across a variety of driving conditions and temperatures
- Delivers and sustains maximum horsepower for longer, even when under pressure

Applications

MOTOSEL Full Synthetic SAE 10W-60 Motor Oil is suitable for use in automobile, gasoline and diesel engines where the manufacturer recommends an ACEA A3/B3, A3/B4, API SP or earlier specification 10W-60 lubricant.

- Meets or exceeds the specifications for BMW M-Models that require a 10W-60 lubricant
- Meets or exceeds the requirement of VW 501 01 / 505 00 specification 10W-60 lubricant



TYPICAL CHARACTERISTIC - 10W-60 FULL SYNTHETIC ENGINE OIL

SAE GRADE		10W-60
API SERVICE		SP
Density @ 15C, Relative	ASTM D4052	0.853
Viscosity, Kinematic 100C	ASTM D445	22.7
Viscosity, CCS -25C (10W)	ASTM D5293	4879
Viscosity, Kinematic 40C	ASTM D445	160
Viscosity Index	ASTM D2270	173
Pour Point	ASTM D97	-39
Flash Point, PMCC	ASTM D93	203
Ash, Sulphated	ASTM D874	1.29

Test Method ASTM - Typical test data are average values only. Minor variations, which do not affect performance, may occur.

HANDLING AND SAFETY INFORMATION - Refer to MOTOSEL (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.

